

## GRUPO DINÁMICO 400 ° C / 2 H.

MODELO	R.P.M	POTENCIA (A)		CUELLO mm.	CAUDAL m <sup>3</sup> / h.	NIVEL SONORO dB(A)
		220V	380V			
400-6/12T-0,75	940/440		1,60/0,55	400	3.500/1.750	53/38
400-4T-0,75	1.410	2,73	1,57	400	5.100	64
450-6/12T-0,75	940/440		1,60/0,55	450	4.570/2.375	55/40
450-4T-0,75	1.410	2,73	1,57	450	7.100	68
500-6/12T-0,75	940/440		1,60/0,55	500	6.800/3.400	57/42
500-4T-1	1.415	3,5	2,03	500	10.000	69
560-4/8T-1,5	1.440/710		2,90/1,40	560	14.000/7.000	74/59
560-4T-1,5	1.430	4,8	2,8	560	14.000	74
630-4/8T-1,5	1.440/710		2,90/1,40	630	17.000/8.500	74/59
630-4T-1,5	1.430	4,8	2,8	630	17.000	74
710-4/8T-1,5	1.440/710		2,90/1,40	710	19.900/9.950	78/63
710-4T-1,5	1.430	4,8	2,8	710	19.900	78
800-4/8T-3	1.415/715		5,20/1,90	800	29.500/14.750	82/67
800-4T-3	1.430	9	5,2	800	29.500	82
800-4/8T-4	1.425/710		6,80/2,20	800	37.000/18.500	83/68
800-4T-4	1.430	11,4	6,6	800	37.000	83
900-4/8T-5,5	1.455/725		9,30/3,40	900	46.500/23.250	89/74
900-4T-5,5	1.435	8,4	4,8	900	46.500	89



En caso de precisar medidas constructivas, pongase en contacto con nuestra oficina técnica.

[attclientes@atosdin.es](mailto:attclientes@atosdin.es)